




## V110 FULLY RUGGED LAPTOP

- 12th Generation Intel® Core™ i7 / i5 vPro® Processor
- 11.6" FHD LumiBond display with Getac sunlight readable technology (1,000 nits) and capacitive touchscreen
- Enhanced enterprise security with Intel® vPro®, Windows disk encryption, TPM 2.0 and many more multi-factor authentication options
- Versatile I/Os connectivity including Thunderbolt™ 4 and docking solutions
- LifeSupport battery swappable technology



V110 3D Demo



## SPECIFICATIONS

### Operating System

Windows 11 Pro

### Mobile Computing Platform

Intel® Core™ i5-1235U Processor  
Max. 4.4GHz with Intel® Turbo Boost Technology  
- 12MB Intel® Smart Cache

### Platform options:

Intel® Core™ i5-1245U vPro® Processor  
Max. 4.4GHz with Intel® Turbo Boost Technology  
- 12MB Intel® Smart Cache

### Intel® Core™ i7-1255U Processor

Max. 4.7GHz with Intel® Turbo Boost Technology  
- 12MB Intel® Smart Cache

### Intel® Core™ i7-1265U vPro® Processor

Max. 4.8GHz with Intel® Turbo Boost Technology  
- 12MB Intel® Smart Cache

### VGA Controller

Intel® Iris® Xe Graphics <sup>i</sup>

### Display

11.6" Wide Viewing Angle TFT LCD FHD (1920 x 1080)

Protection film

1,000 nits LumiBond display with

Getac sunlight readable technology

Capacitive multi-touch screen

### Storage & Memory

8GB DDR4

Optional: 16GB / 32GB / 64GB DDR4

### 256GB PCIe NVMe SSD

Optional: 512GB / 1TB / 2TB PCIe NVMe SSD

### Keyboard

LED backlit membrane keyboard

Optional: Rubber keyboard

Power button

5 tablet programmable buttons

### Pointing Device

Touchscreen

- Capacitive multi-touch screen

- Optional: Dual mode touchscreen (multi-touch and digitizer)

Touchpad

- Glide touchpad with left-click and right-click buttons

### Expansion Slot

Smart card reader <sup>ii</sup>

Optional: SD Card + Smart card reader <sup>ii</sup>

Optional: 1D/2D imager barcode reader <sup>ii</sup>

### I/O Interface

5MP webcam x 1 <sup>iii</sup>

Audio in/out combo x 1

DC in Jack x 1

Thunderbolt™ 4 Type-C x 1

USB 3.2 Gen 2 Type-A x 2

LAN (RJ45) x 1

HDMI 2.0 x 1

Serial port (9-pin; D-sub) x 1

Docking connector x 1

Optional: SIM card slot x 1 (Mini-SIM, 2FF) <sup>iv</sup>

Optional: Windows Hello face-authentication

FHD camera (front-facing) x 1 <sup>iii</sup>

Optional: RF antenna pass-through for GPS,

WWAN and WLAN

Optional: 8MP auto focus rear camera x 1

### Communication Interface

10/100/1000 base-T Ethernet

Intel® Wi-Fi 6E AX211, 802.11ax

Bluetooth (V5.3) <sup>v</sup>

Optional: Dedicated GPS <sup>vii</sup>

Optional: 4G LTE mobile broadband <sup>vi, iv, xvi</sup>

Optional: 5G Sub-6 <sup>iv, vi, xvi</sup>

Dual SIM (Mini-SIM 2FF and e-SIM) <sup>vi</sup>

### Security Feature

TPM 2.0

Kensington lock

Optional: Intel® vPro® Technology

Optional: Fingerprint reader

Optional: HF RFID reader <sup>vii</sup>

Smart card reader

Optional: Windows Hello face-authentication

FHD camera (front-facing) <sup>iii</sup>

### Power

AC adapter (65W, 100-240VAC, 50/60Hz)

Li-ion battery (11.1V, typical 2100mAh; min. 2040mAh) x 2

LifeSupport™ battery swappable technology

### Dimension (W x D x H) & Weight

313 x 238 x 39mm (12.32" x 9.37" x 1.53")

2.1kg (4.63lbs) <sup>viii</sup>

### Rugged Feature

MIL-STD-810H certified

IP65 certified

MIL-STD-461G certified <sup>ix</sup>

Vibration & 4ft (1.2m) drop resistant <sup>x</sup>

Optional: ANSI/UL 121201, CSA C22.2 NO. 213 (Class I, Division 2, Groups A, B, C, D) <sup>xi</sup>

Optional: Salt fog certified

### Environmental Specification

Temperature <sup>xii</sup>

- Operating: -29°C to 63°C / -20°F to 145°F

- Storage: -51°C to 71°C / -60°F to 160°F

Humidity:

- 95% RH, non-condensing

### Pre-installed Software

Getac Utility

Getac Camera

Getac Geolocation

Getac Barcode Manager <sup>xiii</sup>

Optional: Absolute Persistence®

### Optional software

Getac Driving Safety Utility

Getac Device Monitoring System (GDMS)

Getac VGPS Utility <sup>xiv</sup>

### Accessories

Battery (11.1V, typical 2100mAh; min. 2040mAh)

AC adapter (65W, 100-240VAC)

Capacitive stylus with tether

### Optional:

Carry bag

Battery (11.1V, typical 2100mAh; min. 2040mAh)

Multi-Bay charger (Dual-Bay)

Multi-Bay charger (Eight-Bay)

AC adapter (65W, 100-240VAC)

Office dock AC adapter (90W, 100-240VAC)

MIL-STD-461 AC adapter (90W, 100-240VAC)

DC-DC vehicle adapter (120W, 11-32VDC)

Digitizer pen with tether

Capacitive stylus with tether

Protection film

Hard handle

X strap

Shoulder strap (2-point)

Vehicle cradle <sup>xv</sup>

Vehicle dock <sup>xv</sup>

Office dock

Spare SSD kit

100W Type-C adapter

Getac rugged keyboard

# V110 FULLY RUGGED LAPTOP

### Bumper-to-Bumper warranty

Accidents can take your equipment out of service when you least expect it, especially in a rugged environment, which can cause costly equipment downtime. That is why Getac has introduced accidental damage as standard under our Bumper-to-Bumper warranty, to help minimize your enterprise IT costs. Bumper-to-Bumper is your hassle-free guarantee. That means you can depend on us to have your unit back in service within days.

### Standard

3 years Bumper-to-Bumper

- I. Units equipped with dual channel memory come with Intel® Iris® Xe Graphics.
- II. Smart card reader, Optional SD card + Smart card reader, and Optional 1D/2D imager barcode reader are mutually exclusive.
- III. 5M webcam and optional Windows Hello face-authentication FHD camera (front-facing) are mutually exclusive options.
- IV. Units with 4G/5G LTE option come with an embedded SIM card slot.
- V. Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area.
- VI. One physical SIM card slot and one eSIM. Network service may vary depending on local telecommunication providers.
- VII. 13.56MHz contactless HF RFID/NFC reader (ISO 15693, 14443 A/B, Mifare and FelCa™ compliant).
- VIII. Weight and dimensions vary from configurations and optional accessories.
- IX. MIL-STD-461 90W AC adapter sold separately.
- X. Drop test results vary from configurations and optional accessories.
- XI. Available with limited configurations and environment conditions.
- XII. Tested by an independent third-party test lab following MIL-STD-810H.
- XIII. Available when barcode reader option is selected.
- XIV. Models require either embedded or standalone GPS module.
- XV. Gamber Johnson and Havis vehicle docks are e-mark certified.
- XVI. Support GLONASS, Galileo, and BeiDou. Only available in US, UK, EU, Australia and New Zealand.

Information provided herewith is for reference only, available specification shall be subjected to quotation by request.

### Contact Information

Guangzhou Huajie Electronic Technology Co., Ltd.

Address: Room 707, Building B1, Creative Building, 162 Science

Becoming the best smart manufacturing partner



	Vehicle Dock	Office Dock
Serial Port	2	2
External VGA	1	1
Microphone	1	1
Audio Output	1	1
DC in Jack	1	1
USB	1	1
LAN	4	4
HDMI	1	1
RF Antenna Connector	3 (WWAN, WLAN, GPS)	--