




## K120 FULLY RUGGED TABLET

- 13th Generation Intel® Core™ i7 / i5 vPro™ Processor
- 12.5" FHD LumiBond display with Getac sunlight readable technology (1,200 nits) and capacitive touchscreen
- Enhanced enterprise security with optional Intel vPro, TPM 2.0, Windows Hello face-authentication 5M camera, and multi-factor authentication options
- Multi-mode usage streamlined by extensive accessory selections
- LifeSupport battery swappable technology
- Thunderbolt™ 4 brings lightning speed and performance



## SPECIFICATIONS

### Operating System

Windows 11 Pro

### Mobile Computing Platform

Intel® Core™ i5-1335U Processor

Max. 4.6GHz with Intel® Turbo Boost Technology

- 12MB Intel® Smart Cache

### Platform options:

Intel® Core™ i5-1345U vPro® Processor

Max. 4.7GHz with Intel® Turbo Boost Technology

- 12MB Intel® Smart Cache

Intel® Core™ i7-1355U Processor

Max. 5.6GHz with Intel® Turbo Boost Technology

- 12MB Intel® Smart Cache

Intel® Core™ i7-1365U vPro® Processor

Max. 5.2GHz with Intel® Turbo Boost Technology

- 12MB Intel® Smart Cache

### VGA Controller

Intel® Iris® Xe Graphics <sup>i</sup>

### Display

12.5" Wide Viewing Angle TFT LCD FHD (1920 x 1080)

Protection film

1,200 nits LumiBond display with

Getac sunlight readable technology

Capacitive multi-touch screen

### Storage & Memory

16GB DDR5

Optional: 32GB / 64GB DDR5

256GB PCIe NVMe SSD

Optional: 512GB / 1TB / 2TB PCIe NVMe SSD

### Keyboard

LED backlit membrane keyboard

Power button

5 tablet programmable buttons

### Pointing Device

Touchscreen

- Capacitive multi-touch screen

- Optional: Dual mode touchscreen (multi-touch and digitizer)

### Expansion Slot

Optional: 1D/2D imager barcode reader

Optional: Serial port (9-pin; D-sub), or USB 3.2 Gen 2

Type-A, or HDMI 2.0

### I/O Interface

#### Tablet

5M pixels webcam x 1 <sup>ii</sup>

8M pixels auto focus rear camera x 1

Audio in/out combo x 1

Optional: MicroSD

USB 3.2 Gen 2 Type-A x 1

Thunderbolt™ 4 Type-C x 2

LAN (RJ45) x 1

Docking connector x 2

Dual SIM (Micro-SIM 3FF and e-SIM) <sup>iii</sup>

Optional: Windows Hello face-authentication 5M camera (front-facing) <sup>ii</sup>

RF antenna pass-through for GPS, WWAN and WLAN

#### Optional keyboard dock:

USB-C charging port x 1

DC in Jack x 1

USB 3.2 Gen 1 Type-A x 3

LAN (RJ45) x 1

HDMI 2.0 x 1

Display port 1.2 x 1

Serial port (9-pin; D-sub) x 1

RF antenna pass-through for GPS, WWAN and WLAN

### Communication Interface

10/100/1000 base-T Ethernet

Intel® WiFi 6E AX211, 802.11ax

Bluetooth (v5.3) <sup>v</sup>

Optional: Dedicated GPS with L1/L5

Optional: 4G LTE mobile broadband with integrated GPS <sup>iii, v</sup>

Optional: 5G Sub-6 with integrated L1/L5 GPS <sup>iii, v</sup>

Dual SIM (Micro-SIM 3FF and e-SIM)

### Security Feature

TPM 2.0

Kensington lock

Optional: Intel® vPro® Technology

Optional: Smart card reader or HF RFID reader or

Fingerprint reader <sup>vi, vii</sup>

Optional: Windows Hello face-authentication 5M camera (front-facing) <sup>ii</sup>

### Power

USB-C AC adapter (65W, 100-240VAC, 50/60Hz)

Li-ion battery

(11.1V, typical 2100mAh; min. 2040mAh) x 2

LifeSupport battery swappable technology

Optional: High capacity Li-ion battery

(14.4V, typical 3450mAh; min. 3300mAh) x 2

### Dimension (W x D x H) & Weight

#### Tablet

329.5 x 238 x 24mm (12.97" x 9.37" x 0.94")

3.13kg (6.9lbs) <sup>viii</sup>

### Tablet + Optional keyboard dock:

340.5 x 327.5 x 47mm (13.40" x 12.89" x 1.85")

3.13kg (6.9lbs) <sup>viii</sup>

### Rugged Feature

MIL-STD-810H certified

IP66 certified

Vibration & 6ft (1.8m) drop-resistant <sup>ix</sup>

Optional: ANSI/UL 121201, CSA C22.2 NO. 213 (Class I, Division 2, Groups A, B, C, D) <sup>x</sup>

### Environmental Specification

Temperature <sup>xi</sup>

- Operating: -29°C to 63°C / -20°F to 145°F

- Storage: -51°C to 71°C / -60°F to 160°F

Humidity:

- 95% RH, non-condensing

### Pre-installed Software

Getac Utility

Getac Camera

Getac Geolocation

Getac Barcode Manager <sup>xii</sup>

Getac Driving Safety Utility (trial version)

Getac KeyWedge Barcode Reader Utility (trial version)

Optional: Absolute Persistence <sup>xii</sup>

### Optional software

Getac Driving Safety Utility

Getac KeyWedge Barcode Reader Utility

Getac Device Monitoring System (GDMS)

Getac VGPS Utility <sup>xiii</sup>

### Accessories

Battery (11.1V, typical 2100mAh; min. 2040mAh)

USB-C AC adapter (65W, 100-240VAC, 50/60Hz)

Capacitive stylus with tether

### Optional:

Carry bag

Battery (11.1V, typical 2100mAh; min. 2040mAh)

High capacity Li-ion battery

(14.4V, typical 3450mAh; min. 3300mAh)

Multi-Bay charger (Dual-Bay)

Multi-Bay charger (Eight-Bay)

USB-C AC adapter (65W, 100-240VAC, 50/60Hz)

Digitizer pen with tether

Capacitive stylus with tether

Protection film

Hard handle

Rotating hand strap with kickstand

Shoulder strap (2-point)

Shoulder harness (4-point; handsfree)

Detachable keyboard

Vehicle cradle <sup>xiv, xv</sup>

Keyboard dock

Vehicle dock <sup>xiv, xv</sup>

Office dock <sup>xv</sup>

Spare SSD kit

Getac rugged keyboard

# K120 FULLY RUGGED TABLET

### Bumper-to-Bumper warranty

Accidents can take your equipment out of service when you least expect it, especially in a rugged environment, which can cause costly equipment downtime.

That is why Getac has introduced accidental damage as standard under our Bumper-to-Bumper warranty, to help minimize your enterprise IT costs.

Bumper-to-Bumper is your hassle-free guarantee. That means you can depend on us to have your unit back in service within days.

### Standard

3 years Bumper-to-Bumper

- I. Units equipped with dual channel memory come with Intel® Iris® Xe Graphics.
- II. 5M webcam and optional Windows Hello face-authentication 5M camera (front-facing) are mutually exclusive options.
- III. One physical SIM card slot and one eSIM. Network service may vary depending on local telecommunication providers.
- IV. Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area.
- V. Support GPS, GLONASS, Galileo, BeiDou and QZSS. Only available in USA, UK, EU, Australia, and New Zealand.
- VI. 13.56MHz HF RFID/NFC reader (ISO 15693, 14443 A/B, Mifare and FeliCa™ compliant).
- VII. Smart card reader, HF RFID reader and Fingerprint scanner are mutually exclusive options.
- VIII. Weight and dimensions vary from configurations and optional accessories; optional high capacity batteries add approx. 11mm (H), 0.20kg.
- IX. Drop test results vary from configurations and optional accessories.
- X. Available with limited configurations and environment conditions.
- XI. Tested by an independent third-party test lab following MIL-STD-810H.
- XII. Available when barcode reader option is selected.
- XIII. Models require either embedded or standalone GPS module.
- XIV. Gamber Johnson and Havis vehicle docks are e-mark certified.
- XV. Available for laptop and tablet mode.

Information provided herewith is for reference only, available specification shall be subjected to quotation by request.

|                      | Vehicle Dock for Tablet Mode  | Vehicle Dock for Laptop Mode  | Office Dock for Tablet Mode   | Office Dock for Laptop Mode   |
|----------------------|-------------------------------|-------------------------------|-------------------------------|-------------------------------|
| Serial Port          | 1                             | 1                             | 1                             | 1                             |
| External VGA         | 1                             | 1                             | 1                             | 1                             |
| Microphone           | -                             | -                             | 1                             | 1                             |
| Audio Output         | -                             | -                             | 1                             | 1                             |
| DC in Jack           | 1                             | 1                             | 1                             | 1                             |
| USB                  | USB 2.0 x 3 USB 3.2 Gen 1 x 3 | USB 2.0 x 3 USB 3.2 Gen 1 x 3 | USB 2.0 x 2 USB 3.2 Gen 1 x 3 | USB 2.0 x 2 USB 3.2 Gen 1 x 3 |
| LAN                  | 2                             | 2                             | 2                             | 2                             |
| HDMI 2.0             | 1                             | 1                             | 1                             | 1                             |
| RF Antenna Connector | 3 (WWAN, WLAN, GPS)           | 3 (WWAN, WLAN, GPS)           | -                             | -                             |
| Kensington Lock      | 1                             | 1                             | 1                             | 1                             |

# Getac