UX10-EX FULLY RUGGED TABLET

- ATEX & IECEx Zone 2/22 explosive atmosphere certified
- 12th Generation Intel® Core™ i5/i7 Processor
- 10.1" Lumibond display with Getac sunlight readable technology (1,000 nits) and capacitive touchscreen with digitizer.
- Enhanced enterprise security with optional Intel vPro®, Windows Hello face-authentication camera and multifactor authentication options.
- Versatile I/Os connectivity including Thunderbolt™ 4.
- Support Wi-Fi, 5G, GPS and LTE performance.

CERTIFIED MIL-STD 810H | INGRESS PROTECTION IP66 | 6' DROP | ATEX | IEC | IECEx

5M webcam / Optional: Windows Hello face-authentication camera

Digitizer Pen

8MP rear camera

Kensington lock

Thunderbolt™ 4 Type-C

USB 3.2 Gen 2 Type-A

Audio in/out combo

DC in Jack

SPECIFICATIONS

Operating System
Windows 11 Pro

Mobile Computing Platform
Intel® Core™ i5-1235U Processor
Max. 4.4GHz with Intel® Turbo Boost Technology
- 12MB Intel® Smart Cache

Platform options:
Intel® Core™ i5-1245U vPro® Processor
Max. 4.4GHz with Intel® Turbo Boost Technology
- 12MB Intel® Smart Cache

Intel® Core™ i7-1255U Processor
Max. 4.7GHz with Intel® Turbo Boost Technology
- 12MB Intel® Smart Cache

Intel® Core™ i7-1265U vPro® Processor
Max. 4.8GHz with Intel® Turbo Boost Technology
- 12MB Intel® Smart Cache

VGA Controller
Intel® UHD Graphics

Display
10.1" Wide Viewing Angle TFT LCD WUXGA (1920 x 1200)
Protection film
1,000 nits LumiBond display with
Getac sunlight readable technology

Storage & Memory
8GB DDR4
Optional: 16GB / 32GB DDR4

256GB PCIe NVMe SSD
Optional: 512GB / 1TB PCIe NVMe SSD

Keyboard
Power button
5 tablet programmable buttons

Pointing Device
Touchscreen
Dual mode touchscreen (multi-touch and digitizer)

Expansion Slot
Optional (top side): 1D/2D imager barcode reader
or HF RFID reader

I/O Interface
5M webcam x 1 [i]
8M pixels auto focus rear camera x 1
Audio in/out combo x 1
DC in Jack x 1
USB 3.2 Gen 2 Type-A x 1
Thunderbolt™ 4 Type-C x 1
Optional: Windows Hello face-authentication camera
(front-facing) x 1 [i]

Communication Interface
Intel® Wi-Fi 6E AX211, 802.11ax
Bluetooth (v5.3) [ii]
Dual SIM (Micro-SIM 3FF and e-SIM) [iii, iv]
Optional: 5G Sub-6 with integrated GPS [iii, iv, v, vi]
Optional: 4G LTE mobile broadband with integrated GPS [iv, v, vi]

Security Feature
TPM 2.0
Kensington lock
Optional: Intel® vPro® Technology
Optional: HF RFID reader [i,ii]
Optional: Windows Hello face-authentication
camera (front-facing) [i]

Power
AC adapter (65W, 100-240VAC, 50/60 Hz)
Li-ion battery (11.1V, typical 4200mAh; min. 4080mAh) x 1
Optional: High capacity Li-ion battery (10.8V, 9240mAh) x 1

Dimension (W x D x H) & Weight
279 x 194.5 x 23.9mm (10.98" x 7.65" x 0.94") [vii]
1.38kg (3.04lbs) [vii]

Rugged Feature
MIL-STD-810H certified
IP66 certified
Vibration & 6ft (1.8m) drop resistant [viii]
ATEX & IECEx certified

Environmental Specification
Temperature [ix] :
- Operating: 0°C to 55°C / 32°F to 131°F
- Storage: -51°C to 71°C / -60°F to 160°F
Humidity:
- 95% RH, non-condensing

Explosion Protection
ATEX/IECEx Zone 2/22
Ex II 3G Ex ic op is IIC T4 Gc
Ex II 3D Ex ic op is IIIC T130°C Dc

Pre-installed Software
Getac Utility
Getac Camera
Getac Geolocation
Getac Barcode Manager
Getac Driving Safety Utility (trial version)
Getac KeyWedge Barcode Reader Utility (trial version)
Optional: Absolute Persistence

Optional software
Getac Driving Safety Utility
Getac KeyWedge Barcode Reader Utility
Getac Device Monitoring System (GDMS)
Getac VGPS Utility [x]

Accessories
Battery (11.1V, typical 4200mAh; min. 4080mAh)
AC adapter (65W, 100-240VAC)
Digitizer pen

Optional:
Battery (11.1V, typical 4200mAh; min. 4080mAh)
High-capacity Li-ion battery (10.8V, 9240 mAh)
Multi-Bay charger (Dual-Bay)
Multi-Bay charger (Eight-Bay)
AC adapter (65W, 100-240VAC)
AC adapter (100W, 100-240VAC)
Digitizer pen
Anti-static protection film
Shoulder strap (2-point)
Shoulder harness (4-point; handsfree)
Rotating hand strap with kickstand

Bumper-to-Bumper warranty
Accidents can take your equipment out of service
when you least expect it, especially in a rugged
environment, which can cause costly equipment
downtime.
That is why Getac has introduced accidental
damage as standard under our
Bumper-to-Bumper warranty, to help minimize
your enterprise IT costs.
Bumper-to-Bumper is your hassle-free guarantee.
That means you can depend on us to have your
unit back in service within days.

Standard
3 years Bumper-to-Bumper

UX10-EX FULLY RUGGED TABLET

I. 5M webcam and optional Windows Hello face-authentication camera (front-facing) are mutually exclusive options.
II. Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area.
III. One physical SIM card slot and one eSIM.
IV. Network service may vary depending on local telecommunication providers.
V. Supports GPS, GLONASS, Galileo, BeiDou and QZSS. Only available in US, UK, EU, AU, and NZ.
VI. Units with 4G/5G option come with an embedded SIM card slot.
VII. Weight and dimensions vary from configurations and optional accessories.
VIII. Drop test results vary from configurations and optional accessories.
IX. Tested by an independent third-party test lab following MIL-STD-810H.
X. Models require either embedded or standalone GPSmodule.

Information provided herewith is for reference only, available specification shall be subjected to quotation by request.

Getac