

Список размеров экструдированных стержней ПТФЭ

Размер счетчика

Внешний диаметр (мм)	допуск внешнего диаметра	Стандартная длина (мм)	Допуск по длине
4	+0.60 -0.00mm	1000 2000	+2.0% -0.0%
5	+0.60 -0.00mm		
6	+0.60 -0.00mm		
7	+0.60 -0.00mm		
8	+0.60 -0.00mm		
9	+0.60 -0.00mm		
10	+6.0 -0.0 %		
11	+6.0 -0.0 %		
12	+6.0 -0.0 %		
13	+6.0 -0.0 %		
14	+6.0 -0.0 %		
15	+6.0 -0.0 %		
16	+6.0 -0.0 %		
17	+6.0 -0.0 %		
18	+6.0 -0.0 %		
20	+6.0 -0.0 %		
22	+6.0 -0.0 %		
25	+6.0 -0.0 %		
30	+6.0 -0.0 %		
35	+6.0 -0.0 %		
40	+6.0 -0.0 %		
45	+6.0 -0.0 %		
50	+6.0 -0.0 %		
55	+6.0 -0.0 %		
60	+6.0 -0.0 %		
65	+6.0 -0.0 %		
70	+6.0 -0.0 %		
75	+6.0 -0.0 %		
80	+6.0 -0.0 %		
85	+6.0 -0.0 %		
90	+6.0 -0.0 %		
95	+6.0 -0.0 %		
100	+6.0 -0.0 %	1000	
110	+6.0 -0.0 %		
120	+6.0 -0.0 %		
130	+6.0 -0.0 %		
140	+6.0 -0.0 %		
150	+6.0 -0.0 %		
160	+6.0 -0.0 %		

Материал: чистый ПТФЭ

Доступны прецизионные заземляющие стержни.

Индивидуальные размеры