

Технические характеристики:

Модель	Тип камеры	Размер подачи	Размер выпуск а (мм)	Производительность (т/ч)								Мощность двигателя (кВт)	Вес (кг)
				8mm	10mm	15mm	20mm	25mm	30mm	35mm	40mm		
	D	40	16	40-50	45-55	60-70	80-90	85-95					
YGP110	Y	100	20	50-55	50-60	70-80	95-105					ye — nn	5800
	M	130	25		55-65	75-90	105-120						
	C	150	25		55-65	75-90	105-120						
	D	40	18	60-70	70-90	80-105	100-125	135-150	160-175	185-200			
YGP220	Y	70	25		90-110	110-130	130-155	160-180	185-210				9300
	M	130	30			140-160	170-190	190-220				IOU ZZU	
	C	210	40				200-220	220-240					
	D	40	25	100-120	110-130	135-155	160-180	190-210	210-235	240-260			
YGP330	Y	100	30	110-130	120-150	165-195:	195-225	230-260	265-295	300-330		160-250	13400
	M	150	40		150-170	205-235	245-275	290-320	325-355				
	C	220	40		150-170	205-235	245-275	290-320	325-355				
	D	50	25		140-160	160-180	190-210	240-260	270-290	310-330	360-370		
YGP550	Y	100	30			230-250	270-290	310-330	340-370	380-410	430-450		26500
	M	150	35			260-280	300-320	340-370	380-410	430-450	450-470	ZUU 0 ID	
	C	230	40			290-310	320-340	380-410	430-460	480-510			

Модель	Тип камеры	Размер подачи (мм)	Размер выпуска (мм)	Производительность (т/ч)						Мощность двигателя (кВт)	Вес (кг)
				20mm	25mm	30mm	35mm	40mm	45mm		
YGP110S	M	200	16	80-90	105-115	120-130	135-145	145-165	155-175	90	7350

			20		120-130	145-155	160-180	170-200	185-215		
	C	250	25			185-195	200-220	210-230			
YGP220S	M	250	18		110-140	140-170	160-190	180-210	200-230	160	10900
			25			170-220	190-240	210-260	230-280		
	C	330	32				230-280	270-320	280-350		
YGP330S	M	280	18		170-190	170-210	190-230	210-255	235-275	250	16200
			25			220-270	255-315	290-345	320-350		
	C	380	32				360-400	380-420	400-440		
			40					450-500	480-530		
YGP550S	M	380	18	325-375	375-425	400-450	425-475	450-500	500-550		33300
			25	500-550	550-600	600-650	650-700	700-750	750-800		
	C	500	32	650-700	700-750	750-800	825-875	900-950		o IO	
			40			900-950	975-1050				